100% CODE COMPLIANT SUSPENDED COVER



Discover the **next generation** of SmartSeam[®] Suspended Cover. **The smart choice for protecting people, products and property from falling dust and debris.**





After 20 years of innovation, the next generation of SmartSeam[®] is here! SmartSeam[®] Suspended Cover and proprietary installation is the only Code Compliant and FM Approved System that meets all of the International Building Code's EC 043-2020 six areas of compliance. The SmartSeam[®] System is fire code compliant, safely containing dust and debris while keeping facilities operational during construction projects and eliminating your liability in case of a fire. Safety, reliability, and best practices make the difference when protecting our clients' people, products, and property.



CODE COMPLIANT

Meets EC 043-2020 document of IBC six areas of code compliance requirements, NFPA 13 and FM 4652 approved.



FLAME RESISTANT

Approved for **installation below sprinkler systems**; Reduces flame and smoke spread



HEAT-REACTIVE SEAM

6' x 5' panels open quickly to allow sprinklers to activate in case of fire.



PROTECTIVE DUST CAP

Protective dust cap over the heat reactive seam provides **extra dust and debris protection**.



ANTISTATIC

Mitigates electrostatic discharges (ESD) to **protect against combustible dust**.



ANTIMICROBIAL Protects against mold, mildew, and bacterial growth.

STRONG 4-PLY MATERIAL

Six mil thick, four-layer polyethylene material provides highest puncture resistance and tear strength.



INNOVATIVE SCRIM DESIGN

Diagonal and perpendicular scrim orientation **resists tearing**.



800.995.4556 | tuffwrap.com *View SmartSeam[®] approved compliance and classifications on the reverse side. TuffWrap[®] and SmartSeam[®] are registered trademarks of TuffWrap Installations, Inc.



AEROSPACE | FOOD & BEVERAGE | INDUSTRIAL & COMMERCIAL | MANUFACTURING | PHARMACEUTICAL | RETAIL | WAREHOUSE & DISTRIBUTION



Properties	Specifications
Material Construction	Four-layer, scrim reinforced, polyethylene that is panelized with a heat-reactive seam.
Protective Dust Cap	Yes
Appearance	Translucent
Nominal Thickness	6 mil
Flame Resistant	Yes
Antimicrobial	Yes
Antistatic	Yes
Load Capacity	10 lbs. / 100 sq. ft.**
Maximum Use Temperature	150°F
Minimum Use Temperature	-70°F
Mullen Burst	45 psi
Grab Tensile	60 lbs. / ft.



	Code Reference	Evaluation Method	
Z	International Building Code IAPMO UNIFORM EVALUATION SERVICES EC 043-2020		
	FM Approved	FM 4652 APPROVED BY FM GLOBAL	

Safety • Liability • Compliance

INTERNATIONAL BUILDING CODE® (IBC®)

TuffWrap SmartSeam® is the only Suspended Cover to fully comply with (IBC) International Building Code's EC 043-2020 six areas of compliance. The new SmartSeam by TuffWrap is the only real choice for companies choosing to protect their brand during reroofing.

Quality	1 Quality	4 Fire Resistance
Strength	Audited manufacturing quality	Flame retardant - Acceptable flame propagation performance
Effectiveness	2 Strength	5 Durability
Fire Resistance	Stays in place; Meets structural performance ASTM E330 procedure A (diff pressure test)	Performs for the duration of the installation
Durability	3 Effectiveness	5 Safety
Safety	Prevents dust/debris from entering protected space	Opens up per code and partially drop: out, but does not impede sprinklers



NEM

800.995.4556 | tuffwrap.com TuffWrap and SmartSeam are registered trademarks of TuffWrap Installations, Inc. (SS21B)

