

# TuffWrap EXT

## TEMPORARY EXTERIOR WALLS



### FLAME RESISTANT

Innovative composition designed to **reduce flame and smoke spread** for temporary exterior walls.



### CUSTOM ENGINEERING

Custom-engineered protection that **covers large openings and spans**.



### PROTECT WORK CREWS

Weather-resistant enclosure creates a **safe interior work environment** that protects against weather.



### EXTEND WORK SEASON

**Reduces downtime** between construction phases and **eliminates weather interruptions**.



### INNOVATIVE SCRIM DESIGN

Diagonal and perpendicular scrim orientation **resists tearing**.



### STRONG 7-PLY MATERIAL

Ten mil thick, seven-layer polyethylene material provides **highest puncture resistance and tear strength**.




### UV RESISTANT

**Protects against degradation** caused by the absorption of UV radiation.

### Installation

Attachment	Full perimeter
Attachment Type (A)	Bar Joists
Attachment Type (B)	Concrete
Attachment Type (C)	W Beam
<30' Wall Height	Reinforcement straps optional*
>30' Wall Height	Reinforcement straps included**



The diagonal scrim is like a ripstop, evenly distributing point loads across the material.

The linear scrim holds installation tension by transferring the load to anchor points on the building.

\* Every project is tailored to our clients' specific needs. Certain projects may require straps.

\*\* Based on building structure



800.995.4556 | [tuffwrap.com](http://tuffwrap.com)

